

Font'N-Aire®





DECORATIVE FLOATING FOUNTAIN

The Nu-Wave floating fountain system was designed for applications where electrical power entering the water is prohibited or undesired. The Nu-Wave is also an excellent choice for very shallow applications. A minimum water depth of nine inches is required. The water is pumped from the body of water through a centrifugal pump and then back to the fountain through a two inch flexible hose. There are no moving parts that can become fouled from debris.

The Nu-Wave fountain assembly consists of a float, nozzle mounting bracket with a two-inch hose connection and your choice of 1 of our 5 decorative spray nozzles.

You have the option to provide your own pump and hoses or you can purchase our optional accessories to complete your fountain system.



NOZZLE PERFORMANCE PUMP REQUIREMENTS

	DIANA NOZZLE						
	SPRAY HEIGHT (ft)	5	10	15	20	25	30
	SPRAY DIAMETER (ft)	5	10	15	20	25	30
	FLOW (GPM)	50	70	85	115	130	190
	NOZZLE HEAD FEET	2.3	18.4	23	27.6	36.8	43.7
	LOAD AMPS	5.6	6.1	7.5	11.8	13.4	21.6
	GALAXY NOZZLE						
	SPRAY HEIGHT (ft)	10	15	20	25	30	35
	SPRAY DIAMETER (ft)	10	30	35	40	45	50
	FLOW (GPM)	55	70	90	100	115	120
	NOZZLE HEAD FEET	9.2	13.8	20.7	27.6	34.5	43.7
	LOAD AMPS	5.3	5.7	6.8	7.3	10.8	12.4
	NORTHSTAR NOZZLE						
	SPRAY HEIGHT (ft)	5	10	15	20	25	30
	SPRAY DIAMETER (ft)	10	30	35	40	45	50
	FLOW (GPM)	60	95	130	140	145	200
	NOZZLE HEAD FEET	9.2	13.8	20.7	27.3	34.5	43.7
And the second s	LOAD AMPS	5.4	6.3	8.4	12.2	21.5	22.5
	NOVA NOZZLE						
	SPRAY HEIGHT (ft)	5	10	15	20	25	30
	SPRAY DIAMETER (ft)	N/A	N/A	N/A	N/A	N/A	N/A
	FLOW (GPM)	50	70	80	115	125	145
pin trus	NOZZLE HEAD FEET	2.3	18.4	23	27.6	36.8	43.7
	LOAD AMPS	5.2	5.5	5.9	7.7	11.3	8.6
	SOLACE NOZZLE						
	SPRAY HEIGHT (ft)	5	10	15	20	25	
	SPRAY DIAMETER (ft)	10	15	20	25	30	
	FLOW (GPM)	60	90	130	145	210	
	NOZZLE HEAD FEET	4.6	18.4	25.3	30	46	
	LOAD AMPS	12.5	8.6	12.2	14.2	23.7	

Contact Air-O-Lator for more details